

HUBER+SUHNER® DATA SHEET

Sencity Art Antenna: 1399.17.0123



Rev.: K

SWA-0859/360/4/10/V_1

Description

Omnidirectional antenna for indoor DAS and inbuilding coverage
Ultra broad band antenna supporting AMPs, CDMA, PCS, UMTS1900, GSM 900, GSM 1800, UMTS, WiFi, WLAN 2400 and 5600, WiMax



For Indoor Use only!

Product Configuration

Technical Data

Electrical Data

	Band 1	Band 2	Band 3	Band 4
Frequency (MHz)	806 - 960	1710 - 2170	2400 - 5600	5600 - 5875
VSWR	1.5	1.5	1.5	2
Gain (dBi)	5	6	7	7
3dB beamwidth (h) (°)	360	360	360	360

General Data

Nominal Impedance	50 Ω
Polarisation	vertical
Connector	N, jack (female), bottom
Composite Power max.	300 W
Ambient Temperature	50 °C

Mechanical Data

Dimensions (mm)	100 x 200 x (Height x Width x Depth)
Weight	0.3 kg

Environmental Data

Operation Temperature (°C)	-40 to 80
IP Rating	
Storage Temperature (°C)	-40 to 80
Transport Temperature (°C)	-40 to 80
RoHS	compliant

Material Data

Radome Colour	
Back Plate/Base Plate Material	Aluminium

Related Products

9091.99.0095 Mounting bracket for SENCITY ART

Related Documents

Mounting Instruction	DOC-0000197543
Painting Instruction	DOC-0000256180
Security Instruction	DOC-0000278984
Outline Drawing1	DOU-00061284.1

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Industrial
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions