

HUBER+SUHNER® DATA SHEET

Within Series Adapter: 31_PC35-50-0-2/199_N

Rev.: J 

Description

Adaptor jack/jack
PC 3.5 jack (female) / PC 3.5 jack (female)

Interface standards
IEC 60169-23



Technical Data

Electrical Data

Impedance	50 Ω		
Interface frequency max.	33 GHz		
Frequency range	DC to 1.5 GHz	1.5 to 6 GHz	6 to 18 GHz
Return loss	≥ 35 dB	≥ 30 dB	≥ 20 dB
Electrical Length	25.5 mm +/- 0.2		

Mechanical Data

Number of matings	500
Weight	0.0055 kg

Environmental Data

Operating Temperature	-65 °C to 90 °C
2002/95/EC (RoHS)	compliant

Material Data

Piece Parts (PC 3.5)

Centre contact	Material	Copper Beryllium Alloy	Surface Plating	SUCOPRO Plating
Outer contact		Stainless Steel		
Body		Stainless Steel		
Insulator		Air Dielectric - Bead - PS		

Piece Parts (PC 3.5)

Centre contact	Material	Copper Beryllium Alloy	Surface Plating	SUCOPRO Plating
Outer contact		Stainless Steel		
Body		Stainless Steel		
Insulator		Air Dielectric - Bead - PS		

Related Documents

Outline drawing	DOU-00013873
-----------------	--------------

Ordering Information

Single package	31_PC35-50-0-2/199_NE
----------------	-----------------------

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions